



Further design and seakeeping investigations into "Enlarged Ship Concept"

J.A. Keuning and Jakob Pinkster

Report 1090-P

March 1997

**Fourth International Conference on Fast Sea Transportation FAST'97,
Sydney, Australia, 21, 22 and 23 July 1997**

REPRODUCED BY: **NTIS**
U.S. Department of Commerce
National Technical Information Service
Springfield, Virginia 22161

TU Delft

Delft University of Technology

Faculty of Mechanical Engineering and Marine Technology
Ship Hydromechanics Laboratory



FOURTH INTERNATIONAL CONFERENCE ON FAST SEA TRANSPORTATION

SYDNEY, AUSTRALIA

JULY 21 – 23, 1997

CONFERENCE PAPERS



VOLUME ONE

PUBLISHED BY



10 Oxford Street, South Yarra
Victoria 3141 Australia
PH: +61 3 9826 8741
FX: +61 3 9827 0704

4A Carmelite Street
London EC4Y 0BN United Kingdom
PH: +44 171 353 1085
FX: +44 171 353 1084

NTIS is authorized to reproduce and sell this report. Permission for further reproduction must be obtained from the copyright owner.

© Copyright 1997 Baird Publications Ltd

VOLUME ONE

INTRODUCTION

Kjell O Holden	xi
<i>International Chairman's Introduction</i>	
Don Lennard	xiii
<i>National Chairman's Introduction</i>	
Neil Baird	xiv
<i>Chairman and Editor-in-Chief, Baird Publications Introduction</i>	

OPENING ADDRESS

Aneurin Hughes	1
<i>The Future of European Shipping Policy</i>	

DEFENCE VESSELS

Andrew Williamson, Alex Tewes	5
<i>Implications for the Royal Australian Navy of Very High Speed Marine Vessels</i>	
Ross Babbage, Tony Armstrong, Ray Toman, Joe Blansjaar	11
<i>Military Fast Vessels for Australia</i>	

RULES AND REGULATIONS 1

Ian Williams	21
<i>The Development and Subsequent Review of the International High Speed Craft Code</i>	
Michael Fan, Miles Pinchin	27
<i>Structural Design of High Speed Craft – a Comparative Study of Classification Requirements</i>	

NUMERICAL ANALYSIS 1

Hideo Orihara, Hideaki Miyata	35
<i>CFD Simulation of a Semi-Planing Boat in Unsteady Motion</i>	
Damien Holloway, Michael Davis	43
<i>Seakeeping Response of a Family of Semi-Swath Hull Forms</i>	

WATERJETS 1

Stephen Turnock, A W Hughes, R Moss, A F Molland	51
<i>Investigation of Hull-Waterjet Flow Interaction</i>	
Gregory Seil, Clive Fletcher, Lawrence Doctors	59
<i>Optimisation of Water-Jet Inlets Using Computational Fluid Dynamics</i>	

CONCEPTS 1

Alexander Day, Lawrence Doctors, Neville Armstrong	65
<i>Concept Evaluation for Large, Very High Speed Vessels</i>	
A F Molland, T Karayannis, P R Couser	77
<i>Concept Exploration and Assessment of Alternative High Speed Ferry Types</i>	
M Basin, Robert Latorre	85
<i>Development of High Speed Craft With Aero-Hydrodynamics Support</i>	

STRUCTURAL DESIGN

Owen Hughes	91
<i>Two First Principles Structural Designs of a Fast Ferry – All-Aluminium and All-Composite</i>	
Mahmood Hossain, Mahiuddin Chowdhury	99
<i>A Beam Model for the Analysis of Hull Girder of Open Deck Fast Ships</i>	
Paul Yakimoff	107
<i>State-of-the-Art Computer Simulation for Structural Analysis of High Speed Catamarans</i>	
Tommaso Coppola, Ernesto Fasano, Masino Mandarino, Armando Turtoro	115
<i>The Restrained Warping Applied to Catamarans</i>	

HULL FORM, RESISTANCE AND APPENDAGES 1

Som Deo Sharma, Xue-Nong Chen	125
<i>Novel Cambered-Hull Catamaran for High Speed in Shallow Water</i>	
Gregory Walker, Anders Fougner, Simon Younger, Tim Roberts	133
<i>Aerodynamics of High Speed Multihull Craft</i>	
Choung Mook Lee, Sang Joon Lee, Young Gi Kim	139
<i>Effect of Free Surface on Lift Characteristics on Fins Attached to a Strut</i>	
Keh-Sik Min, Seon-Hyung Kang	145
<i>Systematic Study on the Hull Form Design and the Resistance Prediction of the Displacement-Type Super-High-Speed Ships (HMRI Super-High-Speed Ship Series)</i>	

PROPULSION 1

Donald Blount	151
<i>Design of Propeller Tunnels for High Speed Craft</i>	
Ulf Dieter Ulken	157
<i>FRP Technology for Propulsion Systems in High Speed Craft</i>	

Please note: Throughout the contents pages the names in bold type are those of the presenting author of the particular paper.

CONTENTS

PROPULSION 1 (continued)

Antonio Sánchez-Caja	167
<i>Partially Submerged Propellers on Fast Large Ships – and Analysis Theory</i>	
Mario Caponnetto, Philip Rolla, Marzio Porro	175
<i>A New Propeller Design Method for Fast Planing Boat Applications</i>	

KEYNOTE ADDRESS

Tor-Christian Mathiesen	187
<i>High Speed Light Craft – a Safe Transportation Concept</i>	

MONOHULLS AND HYBRIDS 1

Giorgio Trincas, Igor Zotti, Octav Kahu, Stefan Totolici	191
<i>Multicriterial Design of Fast Monohulls for the Adriatic Shortsea Shipping Network</i>	
J A Keuning, Jakob Pinkster	201
<i>Further Design and Seakeeping Investigations Into the "Enlarged Ship Concept"</i>	

STRUCTURAL DESIGN: FATIGUE 1

A Fyfe, G L Hawkins, R A Shenoi, W G Price, P Temarel, P J Read, J Kecsmar	209
<i>Fatigue Performance of Welded Aluminium Tee Connections</i>	
Albert Fredriksen	217
<i>Fatigue Aspects of High Speed Craft</i>	

OPTIMISATION 1

Heinrich Söding	225
<i>Drastic Resistance Reductions in Catamarans by Staggered Hulls</i>	
Grant Hearn, Peter Wright	231
<i>Seakeeping for Design: Optimisation of Motion Responses and Wave-Making Resistance of Catamarans via the Application of a Genetic Algorithm</i>	

OPERATIONS 1

Tony White	241
<i>High Speed Ferry Operators on a Global Circuit</i>	
Geoffrey Ede	245
<i>Air Cushion Vehicles – Hovercraft</i>	

MONOHULLS AND HYBRIDS 2

Heikki Sipilä, Anthony Brown	247
<i>Application of the Slender Monohull in High Speed Container Vessels</i>	

STRUCTURAL DESIGN: FATIGUE 2

Are Johan Berstad, Carl M Larsen	255
<i>Fatigue Crack Growth in the Hull Structure of High Speed Vessels</i>	
L A Hicks, S D Clark, R A Shenoi, H G Allen, R M Cripps	263
<i>Fatigue Assessment of High Performance Small Craft Incorporating FRP Sandwich Materials</i>	

OPTIMISATION 2

Andreas Fiehmke, Armin Jesse, Jürgen Jokat, Thomas Schellin	269
<i>Hydrodynamics, Structural Optimisation and Noise Control of a Fast Monohull Ferry Design</i>	

OPERATIONS 2

Roger Syms	277
<i>Specifically Designed High Speed Simulation and the Future of High Speed Training at the Australian Maritime College</i>	

HYDROFOILS

Peter Payne	283
<i>On the Maximum Speed of the Dynafoil</i>	
Frans van Walree	291
<i>A New Computational Method for the Hydrodynamic Performance of Hydrofoil Craft</i>	
Kourosh Koushan, Claus Kruppa	299
<i>Channel Corrections for Model Experiments With Hydrofoils</i>	

TESTING TECHNIQUES 1

Tim Roberts, Nigel Watson, Michael Davis	311
<i>Evaluation of Sea Loads in High Speed Catamarans</i>	
Kari Kyyrö, Matti Hakala, Heikki Helasharju, Antti Rantanen, Timo Holopainen	317
<i>Determination of Structural Dimensioning Loads of a Fast Catamaran Using Rigid-Backbone Segmented Model Testing Technique</i>	
Fai Cheng	325
<i>Some Results From LR's Open Water Model Experiments for High Speed Craft</i>	

HYDRODYNAMICS: MONOHULLS

Susanne Abrahamsson	333
<i>Design Parameters Influencing the Manoeuvrability of Waterjet Propelled Vessels</i>	
Stefan Harries, Detlef Schulze	339
<i>Numerical Investigation of a Systematic Model Series for the Design of Fast Monohulls</i>	
Kim Branner, Bengt Sangberg	349
<i>Hydrodynamic Behaviour, Comparison and Load Application Concerning a Transatlantic High Speed Container Vessel</i>	

ECONOMICS

Jürgen Isensee, Volker Betram, Harald Keil	361
<i>Energy Efficiency and Pollution: a Comparison of Ships and Other Vehicles</i>	
Hiroharu Kato	367
<i>Performance of High Speed Craft in Comparison With Aircraft</i>	
William Hockberger	373
<i>An Economic Framework for Fast Ferry Selection</i>	

SAFETY 1

Chengi Kuo	381
<i>Application of the Safety Case Concept to High Speed Craft</i>	
Alexander Bogdanov, Alexander Maskalik	387
<i>To the Question on Safety Criteria for a New Fast Sea Transport Means – An Ekranoplan</i>	
Oi-Hyun Kim, Ick-Hung Choe, Jae-Hyun Kim, Joon-Mo Choung	391
<i>Bow Collision Analysis of High Speed Passenger Craft</i>	
Adam Brumley, Leonard Koss	397
<i>The Need for Statistics on the Human Behaviour of Passengers During the Evacuation of High Speed Craft</i>	

SLAMMING

Emmanuel Fontaine, Stéphane Cordier	405
<i>Recent Experience Using High Speed Slender Body Theory</i>	
Manolis Samuelides, Georgios Katsaounis	413
<i>Experimental Modelling of Wet-Deck Slamming</i>	

SLAMMING (continued)

Elin Marita Haugen, Odd Faltinsen, Jan Vidar Aarsnes	423
<i>Application of Theoretical and Experimental Studies of Wave Impact to Wetdeck Slamming</i>	
Rong Zhao, Odd Faltinsen, Herbjørn Haslum	431
<i>a Simplified Non-Linear Analysis of a High-Speed Planing Craft in Calm Water</i>	

MOTIONS AND STRUCTURAL LOADS

Riaan van't Veer	439
<i>Analysis of Motions and Loads on a Catamaran Vessel in Regular and Irregular Waves</i>	
Ole Hermundstad, Jan Aarsnes, Torgier Moan	447
<i>Hydroelastic Analysis of High Speed Catamarans in Irregular Waves</i>	
David Kring, D A Mantzaris, G B Tcheou, P D Scavounos	455
<i>A Time-Domain Seakeeping Simulation for Fast Ships</i>	
Martin Renilson, Vincent Anderson	436
<i>Deck Diving of Catamarans in Following Seas</i>	

ENVIRONMENT

Henrik Kofoed-Hansen, Arne Christian Mikkelsen	471
<i>Wake Wash from Fast Ferries in Denmark</i>	
John Ødegaard, Ole Winther Nielsen, Allan Gosling	479
<i>External Noise From Fast Ferries</i>	
Thomas Ibbott, Michael Davis, Will Trondl, Timothy Roberts	485
<i>Performance of High Speed Solar Catamarans</i>	
John Millett, Colin Anderson	493
<i>Fighting Fast Ferry Fouling</i>	

VOLUME TWO**KEYNOTE ADDRESS**

Arne Osmundsvaag	497
<i>Fundamentals of the Fast Ferry Market</i>	

WIGS 1

Syozo Kubo, Kirill Rozhdestvensky	503
<i>An Outline of Conceptual Design and Feasibility Analysis of a Flying Wing Configuration on the Basis of Extreme Ground Effect Theory</i>	
Ho Hwan Chun, Chong Hee Chang, Kwang June Paik, Shin Ik Chang	513
<i>Preliminary Design of a 20 Passenger Parwig Craft and Construction of a 1/10 Scale Radio Controlled Model</i>	

RULES AND REGULATIONS 2

Per Werenskiold	521
<i>Evaluation and Quantification of the Hsc Safety for Approval and Operational Purposes</i>	
Robert Curry, Todd Grove, Andrew Mak	527
<i>Revised Classification Requirements for the Design and Construction of the Latest Generation of High Speed Ferries</i>	

NUMERICAL ANALYSIS 2

Lars Larsson, Carl-Erik Janson, Philippe Brun	537
<i>A Numerical Investigation of Trimaran Configurations</i>	

NUMERICAL ANALYSIS 2 (continued)

Mehmet Atlar, Farhad Kenevissi, Ehsan Mesbahi, 545
Tony Roskilly
*Alternative Time Domain Techniques for Multi-Hull
Motion Response Prediction*

MATERIALS 1

Hisashi Ito, Kota Shibasaki, Motonori Matsuo, 553
Akiyoshi Mizuta, Hironori Sugimoto
*Cavitation Erosion Tests of High Tensile Stainless Steels for
the Techno-Superliner (TSL-F) Hulls*

Derek Russell, Richard Jones, Ian Jones 559
*Developments in Welding Techniques for
Aluminium Alloys*

WIGS 2

Myung-Soo Shin, Seung-Il Yang, Young-Ryeol Joo, 565
Sang-Keun Kim, Young-Soo Bae, Jeong-Hwan Kim,
Ho-Hwan Chun
*Wind Tunnel Test Results for Eight and Twenty Passenger
Class Wing-in-Ground Effect Ships*

RULES AND REGULATIONS 3

Ronald Lokites, Chris McKesson 571
*High Speed Vessels in the USA: An Introduction to the
United States' Regulatory Environment*

NUMERICAL ANALYSIS 3

Dario Bruzzone, Pasquale Cassella, Claudio Pensa, 581
Antonio Scamardella, Igor Zotti
*On the Hydrodynamic Characteristics of a High-Speed
Catamaran With Round-Bilge Hull: Wave Resistance and
Wave Pattern Experimental Tests and Numerical
Calculations*

MATERIALS 2

Ronnal Reichard, Thomas Neyhart 591
*Development of a Composite Superstructure System:
A Joint US Government/Industry Project*

Michael O'Donnell 599
*Polymide Foam Marine Insulation Systems –
Weight Reduction in Non-Structural Systems for
Weight Sensitive Marine Vessels*

KEYNOTE ADDRESS

Alice White 607
Crisis Management

CONCEPTS 2

Kazuo Suzuki, Yuji Nakata, Mitsuhisa Ikenata, 611
Hisashi Kai
*Numerical Prediction on Wave Making Resistance of High
Speed Trimaran*

Christine Schleicher, Dean Schleicher, 623
John Zselezcky
Investigation of a Hybrid Wave Piercing Planing Hull Form

STRUCTURAL DESIGN: FATIGUE 3

S Di, Don Kelly, D Kastak, M Chowdhury, P Goss, 629
Avraham Berkovits
*Development of Generic Ship Models for the Study of
Fatigue in Welded Aluminium Catamaran Structures*

Bård Wathne Tveiten, Torgeir Moan 637
Fatigue of Aluminium Stiffener-Girder Connections

OPTIMISATION 3

L Lazauskas, Ernie Tuck 647
*Low Drag Multihulls for Sporting, Commercial
and Military Applications*

Dugald Peacock, Warren Smith, Prabhat Pal 653
*Minimal Ship Motion Hull-Form Design for High Speed
Using Multi-Criterion Optimisation Techniques*

WATERJETS 2

Tom van Terwisga 661
*A Parametric Propulsion Prediction Method for Waterjet
Driven Craft*

Jason Roberts, Gregory Walker, Michael Davis 669
Flow Distribution at Waterjet Intakes

Tatsuo Kashiwadani 677
*On the Design Method of Waterjet Inlet for the SES
'Meguro 2'*

SURFACE EFFECT SHIPS (SES)

Dario Boote, Massimo Figari, Riccardo Damonte, 685
Raffaele Iaccarino
*Structural Analysis Procedure for Large Size
Surface Effect Ships*

Geert Kapsenberg, Dag McGeorge, Torgeir Vada 699
Global Loads on a Large Size Surface Effect Ship

Hiroomi Ozawa, Hideo Yamaga, Kazuyuki Kihara, 707
Shin Horiba
*The Third Stage of TSL-A Program - TSL-A 'Hisho' and
High-Speed Cargo Handling System*

TESTING TECHNIQUES 2

Nigel Watson , Michael Davis, Tom Roberts	713
<i>Shipborne Measurement of Sea Conditions and Seakeeping Response of High Speed Ferries</i>	
J F Leguen , G Babaud, Etienne Thiberge	719
<i>High Speed Monohulls – Experimental Determination of Loads on Structure by Models and Full Scale Tests</i>	
Larissa Deck	731
<i>Design and Construction of an Open Water Tow Testing Facility</i>	
Jacqueline Rovere	737
<i>Catamaran Resistance From Tests on a Single Demihull</i>	

HULL FORM, RESISTANCE AND APPENDAGES 2

Lawrence Doctors , Alexander Day	743
<i>Resistance Prediction for Transom-Stern Vessels</i>	
Dominic Cusanelli , Garbor Karafiath	751
<i>Integrated Wedge-Flap for Enhanced Powering Performance</i>	
Patrick Couser , A F Molland, Neville Armstrong, I K Utama	765
<i>Calm Water Powering Predictions for High-Speed Catamarans</i>	
James Rintoul	775
<i>Minimisation of Sea-Inlet Resistance of Fast Craft</i>	

CREW AND PASSENGER COMFORT

Moon Seung Kim , Ho Hwan Chun, Young Ryeol Joo	783
<i>Design of a High Speed Coastal Passenger Catamaran With a Superior Seakeeping Quality</i>	
Rohan Smith , Leonard Koss	791
<i>Motion Sickness Study on Wavepiercing Catamarans</i>	
Alan Haywood , Alec Duncan	797
<i>Experiences Using System Identification Techniques on High Speed Ferries</i>	

KEYNOTE ADDRESS

Loren Rosenthal	805
<i>An Overview of the Aviation Safety Reporting System (ASRS)</i>	
John Rothwell	809
<i>The Wizards of AUS</i>	

MATERIALS 3

Bjørn Høyning , Jon Taby	811
<i>Fire Protection of Composite Vessels: Fire Protection and Structural Integrity – An Integrated Approach</i>	

PROPULSION 2

Jan Szantyr	817
<i>Experimental Study of Surface Piercing Propellers for a Patrol Boat</i>	

APPENDICES

Appendix A (Volumes 1 and 2)	
<i>Index of Authors</i>	
Appendix B (Volume 2 only)	
<i>Index of Presenting Authors and their contact details</i>	

FURTHER DESIGN AND SEAKEEPING INVESTIGATIONS INTO THE "ENLARGED SHIP CONCEPT"

J A Keuning Delft University of Technology, The Netherlands
Jakob Pinkster Delft University of Technology, The Netherlands

ABSTRACT

The "Enlarged Ship" Concept, (ESC), as previously introduced by Keuning and Pinkster (1995) as a serious improved fast monohull concept, is now expanded upon with subsequent model testing, in irregular head waves, of a number of such design concepts. The effect of a modified bow shape, made possible by the ESC, is also investigated and evaluated with regard to its possible impact on operability in a seaway. Also the vessel resistance is measured and compared with the previously predicted improvements.

Parallel to the model testing, calculations are carried out with both linear (SEAWAY) and non linear codes (FASTSHIP) to predict heave and pitch motions and, in particular, the distribution of the peak vertical accelerations. Finally, an economic appraisal of the designs is also shown.

1 INTRODUCTION

A monohull sailing at high forward speed in head waves may incur unacceptably high levels of vertical accelerations. This may hamper the safe operability of the craft.

To optimise the seakeeping behaviour of one particular fast monohull design, the authors have explored the so-called "Enlarged Ship Concept", (ESC), Keuning and Pinkster (1995). In this concept the resistance and more in particular the seakeeping behaviour of a vessel is optimised by increasing the length and so increase the length to beam ratio, reducing the running trim under speed and improving the general layout of the ship. The work carried out then was based on a desk study, concerning three design concepts, namely a base boat with two Enlarged Ship configurations. Results from this study were very promising and favoured the Enlarged Ship Concept.

In the present paper, the same topic is now expanded upon further with subsequent model testing of four such design concepts, made possible by the fact that the ESC's are presently of interest to the shipbuilding community of such fast vessels in the Netherlands. Included within these tests, is the effect of a modified bow shape, made possible by applying the Enlarged Ship Concept.

The motions of the ESC in a seaway have already been improved by the introduction of the very specific features of the concept, i.e. increasing length, less trim, higher length-displacement ratio and shifting the wheelhouse relatively aft etc., but the workability is further increased by introducing bow modifications, i.e. reducing sectional flare and areas.

The philosophy behind these bow modifications is based on the real world observation that the operability of fast ships in a seaway is really limited by the (single) occurrence of very high peak values in the vertical accelerations, either at the bow, possible cause of structural damage or at the wheelhouse, possibly causing human injuries. The (single) occurrence of these very high peaks in the vertical accelerations provokes the crew to a "voluntary" speed reduction to prevent it "from happening again". This reduction action is undertaken irrespective of the momentary significant level of the vertical accelerations.

So, increasing the operability of a high speed vessel may be directly coupled to avoiding these very high peak values as much and as long as possible.

Many optimisation studies of high speed vessels however are based on comparison of significant acceleration levels only. This is initiated by the fact that the criteria used for the determination of the boundaries of safe operation of these fast vessels are generally based on the prevailing level of significant vertical accelerations in a seaway. The Dutch National Authority, for instance, still uses the threshold value of $av^{1/3} < 0.35$ g at the wheelhouse for her ships. The use of such threshold values based on the level of significant vertical accelerations, which for a signal with Rayleigh distributed peaks and troughs have a probability of exceedance of approximately 13.5%, would be quite acceptable if there is a well defined relation between these and the occurrence of the extremes in the vertical accelerations with for instance a probability of exceedance smaller than 0.1%. For a Rayleigh distribution this relation exists and since the surface waves are generally supposed to be Rayleigh distributed the same could hold true for the vertical accelerations if a fast moving monohull in waves is a linear system.

However it is well known that a fast moving monohull in a seaway is not a linear system. Therefore as shown by, amongst others, Keuning (1994), this distribution of peaks in the vertical acceleration is strongly dependent on hull geometry, general arrangement and forward speed and must therefore be determined for each individual design. On the other hand therefore, it may also be influenced through design optimisations.

A clear demonstration of this is presented in Figure 1, from Ooms and Keuning (1997), in which the maximum measured values of the vertical acceleration in the wheelhouse of a fast Dutch pilot vessel, during a large number of full-scale test runs of 10 minutes duration in waves, is plotted on basis of the RMS of the same signal. The dotted line represents the approximation based on linear theory assuming the surface waves are Rayleigh distributed. The deviation of the linear theory is obvious. The maximum values of the peak accelerations (or their frequency of occurrence) is much higher than predicted by assuming that the system of a fast planing monohull in waves behaves linearly.




Figure 1: Relation between vertical acceleration peaks and RMS values

The deliberately created large area of "void space" in the forepart of the Enlarged Ship makes it possible to modify the bow sections in such a way that these high wave induced- and dynamic-lift forces are lowered in an effort to reduce the non-linear behaviour of the vessel and therewith these very high peak values. A similar improvement is at the same time achieved by moving the accommodation and more in particular the wheelhouse, which retain the same physical length on an otherwise lengthened ship in the ESC approach, relatively backwards along the length of the ship into the area of smaller overall motions and accelerations, see Figure 2.




Figure 2: Base boat and alternative ESC designs

The best way of determining the above mentioned distributions of vertical accelerations at different locations on the ships is by way of model experiments. Therefore model tests are carried out to determine these vertical acceleration levels encountered due to ship motions. Different wave spectra are used during these experiments. All testing is done in irregular waves. Additional calm water tests have also been carried out to determine the resistance, sinkage and trim.

Motion calculations are further carried out with both linear (SEAWAY) and non linear codes (FASTSHIP) which have been

developed at the Delft University of Technology, Ship Hydrodynamics Laboratory in order to assess the possibility to predict these distributions and the occurrence of high peak values.

The effect of the change in bow configuration on vertical acceleration levels in irregular head seas is quantified. The overall improvement in both resistance and operability, to be achieved by applying the Enlarged Ship Concept including bow modifications is evaluated using these results. Economic appraisals of the designs are also made for a given mission profile.

2 THE "BASE BOAT"

As basic monohull, as described by Keuning and Pinkster (1995), an existing semi-planning fast patrol boat (Royal Hong Kong Police 'King Class' 26 m., speed 25 knots) has again been chosen. This vessel is a well proven design from the Damen Shipyard Group of the Netherlands and has been described in more detail in the aforementioned reference. All design and functional requirements, such as speed, payload, accommodations etc., for the Enlarged Ship Concepts are based on and kept identical to those of this base boat.

Relevant design information regarding hull form, stability and trim, weights, building costs etc. of the basic monohull were kindly made especially available to the authors for the work carried out here. The main vessel design particulars are listed in Table 1.

3 THE "ENLARGED SHIP" DESIGNS

To yield the design of the Enlarged Ship Concepts for this study the basic Stan Patrol 2600 design, forthwith designated "2600", is enlarged in length only. Two such designs (alternatives "3500" and "4100") are made, each having a length of respectively 35 m., and 41 m. Each vessel has been increased in length by respectively 35% and 58% with respect to the basic design. A fourth design alternative, "TUD4100", has the same length as design alternative "4100" and is furthermore fitted with a highly different bow shape.

With regard to engineering of all these alternatives the starting point was relative data related to the base boat. The increase in length was created by stretching the original body plan using the respective length factors of 1.35 and 1.58. The body plan remains practically speaking the same for the first three designs with the exception however regarding the number of frames (frames pacing = 1 m. for all designs computed) and their longitudinal positions. Design "TUD4100" has, of course, different (sharper and longer) lines in the bow. Subsequently hydrostatic particulars were computed for the new body plans. The increase in structural weights of all alternatives was also computed via the original weight data which was augmented with extra frames and hull plating while, at the same time, taking into account the relevant positions of the centres of gravity of all components of the designs. The resistance and propulsion calculations were also made for each alternative and the position of the system centre of gravity of each design was such that a 0.5 degree trim-angle (down by the stern) at zero speed was obtained.

Since the idea behind the Enlarged Ship Concept is equal payload for all possible alternatives it stands to reason that the vessel configuration (ie. also position of accommodations, wheelhouse etc. with respect to the stern) remains largely

Table 1: Main Particulars of the different designs

		BASIC DESIGN ALTERNATIVES			
		2600	3500	4100	TUD4100
Length o.a.	[m]	26.70	35.70	41.70	41.70
Length waterline	[m]	23.40	31.60	36.90	38.20
Beam moulded	[m]	5.80	5.80	5.80	5.80
Depth moulded	[m]	3.35	3.35	3.35	3.35
Draught midships	[m]	1.62	1.46	1.38	1.43
Displacement	[kN]	970	1058	1115	1115
Deadweight	[kN]	170	170	170	170
Speed	[knots]	25	25	25	25
Total engine power	[kW]	2000	1446	1500	1536




Figure 3: Lines plan for the "3500" and "TUD4100" design alternatives

unchanged to that of the basic design for each design alternative concerned.

All enlarged alternatives are shown in Figure 2 along with the base boat configuration. The main design particulars for the alternative designs are shown in Table 1. A simple lines plan is shown for the "3500" and "TUD4100" with highly different bow shape in Figure 3.

The reasoning behind the new bow-shape for the Enlarged Ship Concept is that the non-linear behaviour of the vessel to a large degree originates from dynamic lift forces and wave exciting forces. The magnitude of the dynamic lift forces is directly related to the change of momentum of the on-coming flow and therefore to the change in added mass of the sections while being sub- and emerged at high forward speed due to non-small relative motions. The mechanism is explained in detail by Keuning (1994).

The same holds true for the wave exciting forces which were by means of comparing measurement and calculations found to be highly dominated by the Froude-Kriloff component when calculated by integration of the undisturbed wave pressure over the actual momentary submerged volume of the ship sections whilst the ship is performing non small relative motions with respect to the waves.

The way sought to diminish these non-linear effects is by reducing both the change in added mass of the sections and the submerged volume of the sections whilst performing large relative motions with respect to the waves. Also deck submergence and bottom emergence should be avoided as much as possible, because they lead to abrupt changes in both. This obviously leads to reducing volume and flair in the sections as much as possible, both below and above the waterline, whilst increasing depth and freeboard as much




Figure 4: Resistance. Calculated and measured results.




Figure 5: Sinkage and trim. Calculated and measured results

as "acceptable". An ultimate design exploitation of this concept could lead to a "wave piercing bow". However, this idea was not further evaluated because of lack of general acceptance by the foreseen ship-owners. Also an "axe-shaped bow" (ie. high positive deck sheer and downwards sloping bottom contour), was not further developed in this stage for the same reason.

As stated by Keuning and Pinkster (1995) and shown in Table 1, is that the larger the design the relatively lighter the ship becomes and to a lesser degree the lower the engine power becomes to propel the vessel at a constant speed of 25 knots. Again, it should be noted, however, that the "base design" is somewhat over-dimensioned with regard to scantlings in view of the working boat philosophy of the designing yard.

4 SHIP RESISTANCE

Vessel resistance, trim angle and rise of centre of gravity (cog), for all models are measured for different speeds in calm water in the range from 10 to 30 knots approximately. The same is calculated with the program FASTSHIP for planing hull forms. The results are shown in Figures 4 and 5 and confirm the tendencies as shown in Reference [1]. Model and calculation results show good agreement for the resistance and reasonable agreement for the sinkage and trim. Of particular interest of the ESC resistance curve when considering the design as a patrol boat is the diminishing existence of a "hump" in the resistance curve, which is quite favourable for a ship to be used at two rather separated

speeds, ie. a cruising speed of about 12 knots and a design speed of 25 knots.

Therefore the advantage of the Enlarged Ship over the smaller ones with respect to resistance and trim remains.

5 SHIP MOTIONS

The experiments with the models of the designs in waves are carried out in the large towing tank of the Delft Ship Hydromechanics Laboratory. The dimensions of this tank are: length 145 metres, width 4.5 metre and water depth 2.5 metre. The tank is equipped with a hydraulically actuated wave generator of the hinged flap type. The towing carriage is capable of attaining speeds up to 8 m/sec.

Ship motions are measured for all models in irregular waves at a forward speed corresponding to the full scale design speed of 25 knots. Four wave climates have been selected, based on data derived from the Ocean Wave Statistics, Hogben and Lumb (1967), for carrying out the comparison. These are:

- 1) $T_p = 5.3$ s $H_{1/3} = 1.26$ m : a condition most frequently encountered at the North Sea,
- 2) $T_p = 8.4$ s $H_{1/3} = 2.95$ m : a condition exceeded only 5% of the time on the North Sea
- 3) $T_p = 5.9$ s $H_{1/3} = 1.29$ m : a condition most frequently encountered in the Caribbean
- 4) $T_p = 10.4$ s $H_{1/3} = 5.5$ m : a condition exceeded only 10% of the time in the Caribbean

The conditions 1 and 3 were considered to be so close together that they have been combined in order to reduce the number of tests to be carried out. The spectra used in the experiments are shown in Figure 6. These spectra are numbered condition 1, 2 and 4 respectively.




Figure 6: Spectra used in the experiments.

Ship motions heave and pitch and the vertical accelerations in three different locations along the length of each model, ie. the wheelhouse, the vessel Centre of Gravity in loaded condition (cog) and the forepeak are measured. Since the aim of the measurements is to differentiate between the different design concepts on a basis of occurrence of extremes in the vertical accelerations, the number of tests-runs in each spectrum has been increased to at least 12, meaning an average encounter between ship and waves of at least 500 waves. Each run has been executed in a different




Figure 7: Weight distribution TUD4100 and values radii of gyration.

part of the spectrum realisation, but for each model the same parts of the realisations have been used to ensure a basis for comparison as similar as possible.

Before carrying out the experiments an analysis has been made of the weight distribution over the length of the various ESC designs in order to assess the differences in the longitudinal radii of gyration. From this analysis it was found that the radius of gyration of these patrol boat is generally lower than expected or used in the motion calculations. As expected in particular the largest ESC, ie. the TUD 4100, has a considerable lower radius of gyration than the generally assumed 25% of LOA. Obviously this lower radius has a significant impact on the natural periods of pitch of the various design variations. In Figure 7 the calculated weight distribution of this ship is presented and in the associated table the various radii for the other designs as used in the experiments and in the calculations are presented.

The results for the heave and pitch motions are presented in Figure 8 in the format of significant values on a basis of the three respective spectra, these being sorted on increasing




Figure 8: Ship motions and vertical accelerations.

significant wave height, in which the measurements have been carried out.

As may be observed from these results the differences in heave between the different models are small and for the pitch motion somewhat bigger both favouring the larger ships. The general trends of these results of the significant values of the motion amplitudes are quite well reproduced by the calculations, in particular by the linear ship motion code SEAWAY.

In Figure 8, also the significant vertical accelerations and the average of the highest three peaks measured during the total tests duration of all runs combined in the wheelhouse and in the bow, are presented for the three spectra.

It should be emphasised that all results are presented using a horizontal scale therefore this includes a change in significant wave height as well as peak period of the spectrum! From these plots it is obvious that the TUD 4100 ESC has significant lower values for the peaks at the wheelhouse in all conditions, even though the difference in significant values between the three designs is much more marginal.

As far as the vertical accelerations in the bow are concerned, it should be realised that these are also dependent on the distance between the point of observation and the centre of gravity of the ship, which is evidently larger for the ESC.

The acceleration levels are both calculated with the linear code (SEAWAY) and non linear codes (FASTSHIP), developed at the Delft University of Technology, Ship hydrodynamics Laboratory. Once again the significant values are quite adequately predicted by the linear code but the extremes are only properly predicted by the non-linear code. The results are shown in Figure 8 and confirm the tendencies as obtained from the measurements and also correspond with the results shown by Keuning and Pinkster (1995).

Considering the assumption that the workability of a fast vessel in waves is strongly dependent on the avoidance of unacceptable high peaks in the vertical accelerations, the improvement obtained by using the ESC with the modified bow is most clearly demonstrated by the results plotted in Figure 9.

In Figure 9, the magnitude of the peaks of the vertical accelerations in the wheelhouse for three of the design concepts, i.e. the "2600", the "3500" and the "TUD4100", is plotted on a basis of percentage of exceedance. For each model, also the assumed Rayleigh distribution of these peaks is plotted for the sake of reference. The level of deviation between the measured distribution from the Rayleigh distribution originates from the non-linearity of the system.

From these plots, it is obvious that, considering a given "threshold" value of the allowable peak of the vertical acceleration, these are rather more frequently encountered in the case of the "3500" and even much more frequently so with the "2600" when compared with the "TUD4100". Also the non-linear behaviour of the "2600" and to a lesser extent of the "3500" is clearly demonstrated by these plots. The ratio between the significant value (approximately 13.5% probability of exceedance) and the maximum value (for instance 0.1% probability of exceedance) is shown to be strongly dependent on this non-linear behaviour and therefore, on the particular design under consideration.

Ship motion calculation codes based on linear theory are not capable of predicting such differences. From calculations carried out with the non-linear FASTSHIP code it turned out that the trends may be predicted although the absolute values may still differ.




Figure 9: Percentage of exceedance of vertical accelerations in wheelhouse

The differences presented between the alternative designs in Figure 9 have an enormous impact on the workability of the vessels. However time did not permit calculations of these differences for a given mission profile in the scope of the present study.

6 ECONOMIC EVALUATION

In order to make an economical evaluation the building costs of the different design alternatives have been estimated. These were estimated using the original building costs of the "2600" (of which all costs components were known) and correcting this for changes in steel weight of the hull and extra painting costs (i.e. cleaning, preparation and painting). The differences in building costs are indexed with regard to the "2600" in Table 2. Note the low increase in building costs of approximately 3% per 25% increase in vessel length.

The operational costs of all the design alternatives are considered for a scenario of a ten year economic life, sailing six hours per day at full speed, seven days a week for 48 weeks per year and crewed by five person (three shifts per 24 hours). The differences in operational costs are indexed with regard to the "2600" in Table 2. Note the relatively high decrease in operational costs of approximately 5% for design alternative "3500". This decrease is less dramatic in the case of the "4100" design alternatives (i.e. 7%).

The transport efficiency (TE) – defined as (payload(kN)* service speed(m/s))/installed power (kW) – has been calculated for all four designs.

The differences in TE are indexed with regard to the "2600" in Table 2. Note the relatively high increase in TE of approximately 38% for "3500" design alternative.

Table 2: Main results of the economic calculations

		BASIC DESIGN ALTERNATIVES			
		2600	3500	4100	TUD4100
Length index	[m]	1.00	1.35	1.58	1.58
Building costs index	[m]	1.00	1.04	1.06	1.07
Operational costs	[m]	1.00	0.95	0.93	0.93
Transport efficiency	[m]	1.00	1.38	1.33	1.30

CONCLUSION

Given the four designs presented in this paper, along with the wave scatter environment, seakeeping criteria and the patrol boat mission profile, the following conclusions are drawn with regard to the enlarged ship concept (see also Table 2):

- Conclusions given by Keuning and Pinkster (1995), are, on the whole, well supported by the results presented in this paper.
- In order to minimise the non-linear behaviour of a fast monohull in waves various design options are available, such as ESC, bow modifications etc.
- Optimisations with respect to workability, using limiting criteria based on significant values of vertical accelerations, may lead to erroneous results.
Peak values of the vertical accelerations should be used rather than significant values.

ACKNOWLEDGEMENT

Although the results and views expressed in this paper are those entirely of the authors, special thanks are due to Mr. Cor Bom, Mr Alex van Gulik, Mr J M J Journée, Mr. Ruud Onnink, Mr Hans Ooms and Mr Rein van den Oever of the Delft Hydromechanics Laboratory of the Technical University Delft for their fine work regarding computations, model testing and evaluation thereof.

REFERENCES

- Journee, J.M.J., (1992), "SEAWAY-Delft, User Manual and Technical Background of Release 4.00", Delft University of Technology, Ship Hydromechanics Laboratory, report no. 910
- Keuning, J.A. (1994), "The Non-linear Behaviour of Fast Monohulls in Head Waves", PhD Thesis, Delft University of Technology – with ref. ISBN 90-370-0109-2
- Keuning, J.A., Pinkster, Jakob, (1995), "Optimisation of the Seakeeping Behaviour of a Fast Monohull", Fast'95 conference, October 1995
- Keuning, J.A., Gerritsma, J., and Terwisga, P.F., (1993), "Resistance Tests of a Series Planing Hull Forms with 30 degrees Deadrise and a Calculation Method Based on this and Similar Series", Int. Shipbuilding Progress, December 1993
- Beukelman, W., (1988), "Prediction of Operability of Fast Semi-planing Vessels in a Seaway", Delft University of Technology, Ship Hydromechanics Laboratory, report no. 700
- Hogben, N., and Lumb, F.E., (1967), "Ocean Wave Statistics", National Physical Laboratory, FWSO, 1967
- Ooms, J., Keuning, J.A., (1997), "Comparative Full Scale Trials of Two Fast Rescue Vessels", SURV IV Conference in Gothenburg, May 1997

J A KEUNING

J A Keuning is an associate professor in the Ship Hydromechanics Laboratory of Delft University of Technology (DUT). He graduated at the Faculty of Maritime Technology of DUT in 1977. After his graduation in 1977, he was R&D project engineer at the Delft Hydraulics Laboratory. In 1979, he became an Assistant Professor in the hydrodynamics department of the Delft University of Technology. He has held the position of Associate Professor since 1990.



In 1994 he obtained his PhD at the same University on the subject of non-linear motions of high speed vessels in head seas. On this subject he has published various papers.

JAKOB PINKSTER

Jakob Pinkster holds a Master's degree in Naval Architecture from the Delft University of Technology. After his graduation in 1979, he was R&D project engineer at Royal Boskalis Westminster Group, R&D project engineer at Damen Shipyards and lecturer at the Polytechnic West Brabant, respectively.



Since 1991, he has held the position of Assistant Professor in the Ship Design Section of the Delft University of Technology. He presents lectures for students on ship design and supervises them in their design and graduation work.

His particular areas of research interest are ship design and advanced marine vehicles, on which subjects he has published various papers.

